

2300 Series



seleccionar	Consulta	Designación de rodamientos	Dimensión (mm)				Capacidades de Clasificaciones carga básicas		de velocidad		Peso (Kg)
			rek	D	B	rs min	cr	cor	Grasa	Aceite (rpm)	
2300	10	35	17	0.6	10.1	2.15	17000	20000	0.083		
2301	12	37	17	1	11.8	2.71	15000	17000	0.091		
2302	15	42	17	1	12	2.9	13000	15000	0.114		
2303	17	47	19	1	14.4	3.55	11000	14000	0.156		
2304	20	52	21	1.1	18.1	4.7	10000	12000	0.206		
2304K	20	52	21	1.1	18.1	4.7	10000	12000	0.201		
2305	25	62	24	1.1	24.4	6.6	8500	10000	0.334		
2305K	25	62	24	1.1	24.4	6.6	8500	10000	0.326		
2306	30	72	27	1.1	31.5	8.75	7200	8500	0.496		
2306K	30	72	27	1.1	31.5	8.75	7200	8500	0.485		
2307	35	80	31	1.5	39.5	11.3	6300	7400	0.671		
2307K	35	80	31	1.5	39.5	11.3	6300	7400	0.653		
2308	40	90	33	1.5	45	13.5	5600	6600	0.918		
2308K	40	90	33	1.5	45	13.5	5600	6600	0.895		
2309	45	100	36	1.5	54	16.7	5000	5900	1.23		
2309K	45	100	36	1.5	54	16.7	5000	5900	1.2		
2310	50	110	40	2	64.5	20.2	4600	5400	1.63		
2310K	50	110	40	2	64.5	20.2	4600	5400	1.59		
2311	55	120	43	2	75.5	24	4200	4900	2.1		

2300 Series

2311K	55	120	43	2	75.5	24	4200	4900	2.05
2312	60	130	46	2.1	87	28.2	3800	4500	2.59
2312K	60	130	46	2.1	87	28.2	3800	4500	2.52
2313	65	140	48	2.1	96	32.5	3600	4200	3.2
2313K	65	140	48	2.1	96	32.5	3600	4200	3.12
2314	70	150	51	2.1	109	37.5	3300	3900	3.92
2315	75	160	55	2.1	123	43	3100	3600	4.78
2315K	75	160	55	2.1	123	43	3100	3600	4.66
2316	80	170	58	2.1	128	45	2900	3400	5.65
2316K	80	170	58	2.1	128	45	2900	3400	5.51
2317	85	180	60	3	140	51.5	2700	3200	6.55