



| Rodamiento No. | Dimensiones límite (mm) |    |    |        | Capacidades de carga básicas (kN) |                | Masa<br>Kg |
|----------------|-------------------------|----|----|--------|-----------------------------------|----------------|------------|
|                | rek                     | D  | B  | rs min | Dinámico(Cr)                      | Estático (Cor) |            |
| 62201          | 12                      | 32 | 14 | 1      | 6.82                              | 3.06           | 0.053      |
| 62202          | 15                      | 35 | 14 | 1      | 7.64                              | 3.72           | 0.065      |
| 62203          | 17                      | 40 | 16 | 1      | 9.57                              | 4.79           | 0.096      |
| 62204          | 20                      | 47 | 18 | 1.5    | 12.84                             | 6.65           | 0.145      |
| 62205          | 25                      | 52 | 18 | 1.5    | 14.02                             | 7.88           | 0.172      |
| 62206          | 30                      | 62 | 20 | 1.5    | 19.46                             | 11.31          | 0.275      |
| 62207          | 35                      | 72 | 23 | 2      | 25.67                             | 15.3           | 0.41       |
| 62208          | 40                      | 80 | 23 | 2      | 29.52                             | 18.14          | 0.616      |
| 62209          | 45                      | 85 | 23 | 2      | 31.67                             | 20.68          | 0.625      |
| 62210          | 50                      | 90 | 23 | 2      | 35.07                             | 23.18          | 0.726      |